

Ultra Thin LED Recess Ceiling Panel Light

120VAC Dimmable and 277VAC non-Dimmable – Round and Square



Description:

The DL-series super thin LED panels come complete with an external driver in a junction box. This allows for standard 120VAC ceiling wiring and pre-drywall installation of the driver. Final installation only requires cutting a hole, plugging in the low voltage connector and clipping in the LED panel. Compatible with conventional triac line voltage dimmers.

Applications:

The DL-series LED thin panel is a very cost effective ceiling downlight with a complete light source and direct install dimmable driver that are easy to install. Perfect for residential and commercial new construction and renovations.

Models:



Specifications:

- Supply: 120VAC for the dimmable and 277VAC for the non-dimmable version.
- CCT: WW(3000K), NW(4200K) or CW(6000K)
- CRI90 for a more natural colour
- 120 Degrees Beam Angle
- Trim: White, Oil Rubbed Bronze, Black or Satin Nickel.
- IP Rating: Damp Location (Showers and Soffits)
- Rated Life: >50,000 hours (approx. 15 years)

Certification:

The LED panel and driver are cETL Listed certified for direct installation in Insulated Ceilings (IC) without any thermal housing. Certified for Damp Locations like showers and soffits.

Catalog No.	Description	Power (Watts)	Light Output (Lumens)	Flange Outer Dimensions (mm - in.)	Mounting H - in.ole Size (mm - in.)
DL-4-9R	4" Round LED Panel	9W	600 Lms	Ø125mm - 4 7/8"	Ø106mm - 4 3/16"
DL-6-12R	6" Round LED Panel	12W	800 Lms	Ø175mm - 6 7/8"	Ø162mm - 6 3/8"
DL-4-9E	4" Square LED Panel	9W	900 Lms	125x125mm - 4 7/8"	106x106mm - 4 3/16"
DL-6-12E	6" Square LED Panel	12W	800 Lms	175x175mm - 6 7/8"	162x162mm - 6 3/8"



AVAILABLE FINISHES:

	WH		BZ
	BK		SN

